



L1 ANSWER 55 OF 72 CA COPYRIGHT 2004 ACS on STN
AN 72:15355 CA
ED Entered STN: 12 May 1984
TI Fire-resistant board
IN Shisko, Walter S.
PA Domtar Ltd.
SO Can., 8 pp.
CODEN: CAXXA4
DT Patent
LA English
CC 57 (Ceramics)
FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	CA 821990		19690902	CA	19670711
AB	A board of mineral wool fiber 50-70, asbestos fiber 5-15, clay, starch, wax, and other conventional additive 5-10%, contains 1-20% unexpanded vermiculite . The board expands on firing, owing to the expansion of unexpanded vermiculite , thereby reducing the heat penetration while retaining sufficient strength to prevent the board from disintegrating. In a standard Underwriters test, the thermal properties of a 5/8-in. board without vermiculite was about equal in thermal cond. to a 1/2 in. (before firing) board contg. 10% unexpanded vermiculite . In another test, a board contg. 8.9% unexpanded vermiculite increased 24% in thickness on firing, while retaining good strength.				
ST	fire resistant board vermiculite; board fire resistant vermiculite; vermiculite fire resistant board				
IT	Building materials (boards, asbestos-mineral wool-vermiculite)				
IT	Mineral wool				

✓

L1 ANSWER 36 OF 72 CA COPYRIGHT 2004 ACS on STN
AN 100:38763 CA
ED Entered STN: 12 May 1984
TI Heat-resistant elastic sheets
PA Ibigawa Electric Industry Co., Ltd., Japan
SO Jpn. Kokai Tokkyo Koho, 6 pp.
CODEN: JKXXAF
DT Patent
LA Japanese
IC D21H005-18; B29J001-02
CC 58-4 (Cement, Concrete, and Related Building Materials)
FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 58144196	A2	19830827	JP 1982-19757	19820212
	JP 02029799	B4	19900702		
PRAI	JP 1982-19757		19820212		

AB Heat-resistant elastic sheets are made from a slurry contg. ceramic fibers 60-85, .alpha.-sepiolite 5-20, **unexpanded vermiculite** 5-22, and an org. binder 5-15% by shaping to sheets, dewatering, drying at 100-110.degree., and pressing. Thus, 8000 mL water was mixed with .alpha.-sepiolite 47, ceramic fibers 205, vermiculite 32 g, an acrylonitrile-butadiene system latex 79, 0.5% polyacrylamide [9003-05-8] coagulant soln. 230, and 10% Al₂(SO₄)₃ soln. 15 mL, shaped to a sheet, dewatered by pressing, dried at 110.degree., and pressed to give a 5 mm-thick sheet having bulk d. 0.7 g/cm³ and high elasticity and heat resistance.

ST sepiolite vermiculite ceramic fiber sheet
IT Rubber, butadiene, uses and miscellaneous
RL: USES (Uses)
(acrylonitrile-, in ceramic fiber elastic